

SHUTTER DETAIL INFORMATION

Based on ASCE-05 170 MPH Wind Load Exposure C or D

FBC 2010

Shutter Type: P= Panel, A= Accordion, R= Roll-up

Tribulation Area= Sq. Ft. of Opening

Definition of **Corner Zone**- 10% of least horizontal dimension or 40% of the mean roof height, whichever is smaller. But not less than 4% of the least horizontal dimension or 3 ft.

| Opening number | Shutter type | | | Shutter NOA's | Shutter length or span | Tribulation Area ft2 | Location | | Fastener edge distance | Opening design Load | | Glass separation | Anchor Type and Spacing | | | | | |
|----------------|--------------|---|---|---------------|------------------------|----------------------|----------|----------|------------------------|---------------------|-----|------------------|-------------------------|--------|------|-------------|-----------------|--|
| | P | A | R | | | | Corner | Interior | | (+) | (-) | | Top | Bottom | Side | FLOOR mount | Build out track | |
| 1 | | | | | | | | | | | | | | | | | | |
| 2 | | | | | | | | | | | | | | | | | | |
| 3 | | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | | | |
| 11 | | | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | | | |
| 13 | | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | | | |
| 15 | | | | | | | | | | | | | | | | | | |

Note: HIGHLIGHT ALL MOUNTING DETAILS ON THE PRODUCT APPROVAL AND INDICATE THE NUMBER OF THE OPENING THAT APPLIES NEXT TO EACH DETAIL